

# Institute of Chemical Engineering

Adres artykułu: <https://iich.gliwice.pl/en/article/optimization-of-the-arrangement-of-short-channel-structures-constituting-the-filling-of-the-catalytic-reactor>

## Optimization of the arrangement of short-channel structures constituting the filling of the catalytic reactor

<b>Publication date:</b>	30.12.2020
<b>Publication title:</b>	<a href="#">Optimization of the arrangement of short-channel structures constituting the filling of the catalytic reactor</a>
<b>Authors:</b>	<a href="#">Anna Gancarczyk</a> , <a href="#">Marzena Iwaniszyn</a> , <a href="#">Katarzyna Sindera</a> , <a href="#">Mateusz Korpyś</a> , <a href="#">Andrzej Kołodziej</a> , <a href="#">Tadeusz Kleszcz</a>
<b>Journal information:</b>	Prace Naukowe Instytutu Inżynierii Chemicznej Polskiej Akademii Nauk
<b>Tags:</b>	<a href="#">short-channel structures</a> , <a href="#">velocity profile</a>

**Abstract:** In order to intensify transport processes, short-channel structural fillings of chemical reactors operating in the laminar flow regime should be characterized by a developing velocity profile in the subsequent sections. The paper discusses the results of numerical calculations concerning the change of the fluid velocity profile depending on the gap width between these structures. It has been shown that for given flow conditions there is an optimal gap width.

## Attachments:

[Zeszyt-24-2020](#) pdf, 3.25 MB

<b>Created at:</b>	04.08.2025
<b>Published by:</b>	Artur Wojdyła
<b>Published at:</b>	05.08.2025 11:41
<b>Number of downloads:</b>	70

Tagi: short-channel structures, velocity profile

# Metryczka

<b>Published by:</b>	Artur Wojdyła
<b>Published at:</b>	05.08.2025 14:38
<b>Number of views:</b>	70