

Institute of Chemical Engineering

Adres artykułu: <https://iich.gliwice.pl/en/article/the-effect-of-deviations-of-process-parameters-from-optimum-parameters-on-the-work-of-catalyst-carriers-in-multi-tubular-reactors>

The effect of deviations of process parameters from optimum parameters on the work of catalyst carriers in multi-tubular reactors

Publication date:	30.12.2015
Publication title:	The effect of deviations of process parameters from optimum parameters on the work of catalyst carriers in multi-tubular reactors
Authors:	Waldemar Krajewski , Krystian Kalinowski , Wincenty Turek
Journal information:	Prace Naukowe Instytutu Inżynierii Chemicznej Polskiej Akademii Nauk
Tags:	multi-tubular reactors , catalyst carriers , entropy

Abstract: Vanadium-titanium catalysts deposited on structural carriers work in industrial multi-tubular reactors most often in conditions deviated from optimum parameters. As a result we observe distinct differences in productivities of the process in individual tubes of the reactor. The effect of deviations from optimum parameters on thermal-flow characteristics of structural catalysts has been presented. A criterion of the minimum generation of the entropy was applied.

Attachments:

[Zeszyt-18-2014](#) pdf, 6.25 MB

Created at:	04.08.2025
Published by:	Artur Wojdyła
Published at:	04.08.2025 12:47
Number of downloads:	117

Tagi: multi-tubular reactors, catalyst carriers, entropy

Metryczka

Published by:	Artur Wojdyła
Published at:	18.09.2025 13:55
Last edited by:	Artur Wojdyła
Last edited at:	18.09.2025 13:58
Number of views:	112