

Institute of Chemical Engineering

Adres artykułu: <https://iich.gliwice.pl/en/article/unveiling-a-differential-sorption-mechanism-for-enhanced-co2-capture-highly-selective-fe2o3-and-fe3o4-based-polyimide-mixed-matrix-membranes-1>

Unveiling a differential-sorption mechanism for enhanced CO₂ capture: Highly selective Fe₂O₃- and Fe₃O₄-based polyimide mixed-matrix membranes

Publication date:	13.02.2026
Publication title:	Unveiling a differential-sorption mechanism for enhanced CO₂ capture: Highly selective Fe₂O₃- and Fe₃O₄-based polyimide mixed-matrix membranes
Authors:	Aleksandra Janusz-Cygan, et al.
Journal information:	Journal of Environmental Chemical Engineering

This study presents a comprehensive investigation of polyimide (PMDA-ODA) nanocomposite membranes incorporating hematite (Fe₂O₃) and magnetite (Fe₃O₄) nanoparticles. Incorporation of these fillers primarily aims to reduce nitrogen permeability by reducing the adsorption of this gas on the membrane surface, thereby enhancing membrane selectivity for the CO₂/N₂ system. The gas separation performance was evaluated using pure CO₂ and N₂ permeation tests, which systematically determined key transport parameters, including permeability, diffusion coefficients, solubility coefficients, and ideal selectivity. The optimal filler content was identified as 5 wt% for Fe₂O₃ and 2 wt% for Fe₃O₄, achieving the highest ideal selectivity values of 76.45 and 98.08, respectively. At these loadings, the corresponding CO₂ permeabilities were 2.60 and 3.07 Barrer. The principal novelty of this work is the introduction and comprehensive investigation of a gas-transport mechanism referred as differential-sorption, which has been applied for mixed matrix membranes for the first time. The transport model was developed to better understand the transport behaviour depending on filler type and loading in polymer matrix. A fundamental assumption of this mechanism is limited sorption of one studied gases, while the second gas transport is stabilized by improved interactions with filler and Knudsen diffusion in magnetic channels. The model accuracy was confirmed through random-walk simulations and benchmarked against experimental results and classical predictions from the Maxwell and Bruggeman models. The strong agreement between

the model and experimental data was further supported by detailed structural and property analyses, including thermogravimetric analysis, scanning electron microscopy, atomic force microscopy, gas sorption studies, and mechanical and magnetic measurements.

Metryczka

Published by:	Marek Tańczyk
Published at:	08.05.2026 11:08
Number of views:	23