

Institute of Chemical Engineering

Adres artykułu: <https://iich.gliwice.pl/en/article/copper-tricomponent-catalysts-application-for-hydrogen-production-from-ethanol-1>

Copper Tricomponent Catalysts Application for Hydrogen Production from Ethanol

Publication date:	30.04.2021
Publication title:	Copper Tricomponent Catalysts Application for Hydrogen Production from Ethanol
Authors:	Maria Kulawska , Łukasz Hamryszak , et al.
Journal information:	Catalysts

The application of copper-based catalysts in the production of pure hydrogen in the steam reforming of ethanol was performed. The tricomponent Cu/Zr catalysts with about 4 mass% addition of nickel, cobalt, or cerium have been prepared in our laboratory. The properties of obtained catalysts were compared with bimetallic Cu/Zr catalyst prepared and tested according to the same procedure. Catalytic tests were carried out in the continuous flow fixed-bed reactor in the wide temperature range of 433–593 K for initial molar ratio of ethanol to water equal to 1:3. Catalysts were characterized by XRD, TPR, CO₂-TPD, and TPO methods. Cu/Zr/Ce catalyst proved to be the best; hydrogen yield reached the value of 400 L/(kgcat. • h), selectivity towards carbon monoxide was below 0.5% and the one towards methane was not detected. Additions of Ni or Co did not bring significant improvement in activity.

Metryczka

Published by:	Marek Tańczyk
Published at:	08.05.2026 15:13
Number of views:	5